

# 93-243

Disposable Nitrile Glove with 15.6"
Extended Cuff



# Extra-long disposable gloves with an elbowlength cuff for superior product and worker protection

- Elbow-length cuff (15.6 inches/395 mm) provides extra security against cross contamination
- Soft, durable nitrile material ensures excellent chemical splash protection with a comfortable feel
- Unique cuff design prevents roll-down
- Textured palm and fingers for confident, secure grip
- Packed in polybags for enhanced product protection



# **Industries**

- Food Processing
- Life Sciences

### **Recommended For**

 Enhanced tactile sensitivity and dexterity, especially for delicate procedures







# 93-243

Disposable Nitrile Glove with 15.6" **Extended Cuff** 

## **TECHNICAL DATA SHEET**

#### **PRODUCT INFORMATION**

FRODUCT IN ORMA	
	93-243
Material	Nitrile
Color	Blue
Glove Design	Chlorinated, Powder-Free, Silicone Free, Fully Textured
Cuff	Beaded
Manufacturing/QMS Audit Standards	ISO 9001:2008
Regulatory/Standards Compliance	Category III, EN ISO 374-1:2016, EN 374:2003, EN 420:2003 + A1:2009, EN ISO 374-5:2016, ISO 9001
Packaging	100 gloves per polybag; 10 polybags per case; 1000 gloves per case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia
User Needs Segment	High Risk
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10), XXL (10.5 - 11)
Sensitisers	<ul> <li>Zinc Dibutyldithiocarbamate (ZDBC)</li> <li>Zinc Diethyldithiocarbamate (ZDEC)</li> </ul>
	Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

#### **PHYSICAL PROPERTIES**

	Typical	Typical Values		
Length (mm/inches)	395 /	395 / 15.6		
Freedom from Holes (Inspection level I)	1.5 <i>A</i>	1.5 AQL		
Palm Thickness (mm/mils)	0.12	0.12 / 4.7		
Finger Thickness (mm/mils)	Thickness (mm/mils) 0.16 / 6.3		ASTM D3767,EN 420	
	BEFORE AGING	AFTER AGING		
Ultimate Tensile Strength (MPa)	≥14	≥ 14	ASTM D412 & D573	
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412	

## **ORDERING INFORMATION**

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Ansell Product Code	93243060	93243070	93243080	93243090	93243100	93243110

#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC T: +1800 800 0444 F: +1800 800 0445

Latin America & Caribbean Region Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 Russia

Ansell PYC Ten. +7 495 258 13 16

**Performance Standards and Regulatory Compliance** 













Ansell,  $^{\odot}$  and  $^{\odot}$  are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking  $^{\odot}$  2020 Ansell Limited. All Rights Reserved.

