

TEGERA® 805

Synthetic glove, 15 gg, carbon, nylon, Cat. II, grey, for precision work

PROPERTIES

Good fingertip sensitivity, flexible, good fit, comfortable, breathable, light

SPECIFICATION

TYPE OF GLOVE ESD gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

LINING MATERIAL 15 gg, Carbon, Nylon

DEXTERITY 5

CUFF STYLE Knitwrist cuff

LENGTH RANGE 220 - 250mm

COLOUR Grey

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Bag with euro slot OUTER MATERIAL
SPECIFICATION Nylon, carbon thread



SIZE	ART. NO.	EAN NO.
6	805-6	7392626007901
7	805-7	7392626007918
8	805-8	7392626007925
9	805-9	7392626007932
10	805-10	7392626016545
11	805-11	7392626060777

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 805

FEATURES

For touchscreen, ESD, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Abrasion injuries, scratches, lacerations, antistatic

PRIMARY ENVIRONMENTS OF USE

Dry environments, clean environments

PRIMARY AREAS OF USE

Assembly, electrical installation, inspection work

PRIMARY INDUSTRIES OF USE

Automotive

TYPE OF WORK

Light weight



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
113XX



IEC 61340-5-1:2016



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-02-02

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 805

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	1	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	X	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

IEC 61340-5-1:2016 Electrostatic Discharge (ESD)
resistance below 1 gigaohm



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
113XX



IEC 61340-5-1:2016



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-02-02

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com